

# PES Spray



PF-50



PR-50

## Details:

Model	Type of Feed	Nozzle orifice Ø mm (in)	Air cap	Atomizing Air pressure MPA (BAR)	Fluid Output ml/min	Air consumption l/min (cfm)	Pattern Width mm (in)	Weight g(lbs)	
PF-50-G04	Gravity	0.4 (0.016)	E2	0.09 (0.9)	8	50 (1.8)	40 (1.6)	207 (0.45)	
PF-50-G06		0.6 (0.024)			25		60 (2.4)		
PF-50-G08		0.8 (0.031)			40		80 (3.1)		
PF-50-G10		1.0 (0.039)			55		100 (3.9)		
PF-50-G12		1.2 (0.047)			80		120 (4.7)		
PF-50-G04		0.4 (0.016)			E4		0.1 (1.0)		10
PF-50-G06		0.6 (0.024)	30	80 (3.1)					
PF-50-G08		0.8 (0.031)	45	100 (3.9)					
PF-50-G10		1.0 (0.039)	60	130 (5.1)					
PF-50-G12		1.2 (0.047)	75	140 (5.5)					
PR-50-G04		0.4 (0.016)	04R	0.24 (2.5)		15			30 (1.1)
PR-50-G06		0.6 (0.024)	06R		35				
PR-50-G10	1.0 (0.039)	10R	80		50 (1.8)				



## P-Mini

### Silicon Spray Gun


<b>Weight:</b>	250 g
<b>Air Pressure:</b>	2.0 kg/cm <sup>2</sup>
<b>Air Consumption:</b>	35-45 l/min
<b>Pattern Width:</b>	150-170 mm
<b>Spray Distance:</b>	100-150 mm
<b>Purpose:</b>	Water Oily Mold Release, Water Transfer Printing Activator, Glasses Coating, etc.



P-Quick - 1/4



P-Y connector 1/4  
P-Y connector 3/8



Coupler 1/4 - 6\*4 pipe

## PES SPRAY TECH PVT. LTD.

736-D , PACE CITY-II , SECTOR 37 , GURGAON , HARYANA – 122002 (INDIA)

TEL: +91 9810354095 , 9910106841

EMAIL : [riaz@pesspray.com](mailto:riaz@pesspray.com) , [aquib@pesspray.com](mailto:aquib@pesspray.com) , [sales@pesspray.com](mailto:sales@pesspray.com)

[www.pesspray.com](http://www.pesspray.com)